

TECHNICAL DATA SHEET

EMC13

Polyisocianic Hardener
Suitable for sealer and polyurethane top coats
speed drying medium / fast
aromatic polyisocyanates
aromatics

Chemical-Physical- parameters

Specific Gravity	(g/cm ³) at 20°C	:	1.00±0.05
------------------	------------------------------	---	-----------

Solid content : 27±1%

Storage:

Keep the cans carefully sealed, in a well-ventilated place and with a temperature controlled between 10-30 °C

Deadline:

12 months from date of manufacture when stored according to directions above

ONLY FOR PROFESSIONAL USE

Page 1 of 1

Printed on 07/08/2017

THE DATA AND INFORMATION ON THIS TECHNICAL DATA SHEET ARE BASED ON OUR BEST KNOWLEDGE AT PRESENT. IT IS THE USER'S RESPONSIBILITY TO MAKE SURE THAT THE PRODUCT MEETS HIS/HER NEEDS IN RELATION TO THE TOOLS USED FOR APPLICATION, THE SURFACES TO BE COATED AND THE ENVIRONMENTAL CONDITIONS FOR APPLICATION.

VERNICI EGIDIO MILESI Sede Legale: Viale Caduti per la Libertà 9, 40050 Ponterivabella di M. San Pietro (BO) ITALY Tel: +39-051 6761657Fax: +39-051 6762074 e-mail: info@egidiomilesi.com