



EM45XX

UNIVERSAL STAINS

Main features of the product:

<ul style="list-style-type: none"> • Can be applied by spray, brush and cloth • Good resistance to light • Excellent transparency • Applicable on all types of wood 	<ul style="list-style-type: none"> • Good resistance to light • dilutable in water and all kinds of organic solvents commonly used in wood products with the exception of gasolines and white spirit
---	--

Versions

EM4501	YELLOW	EM4508	ROSEWOOD
EM4502	ORANGE	EM4509	GREEN WALNUT
EM4503	RED	EM4510	WALNUT
EM4504	BRIGHT RED	EM4511	MEDIUM WALNUT
EM4505	BLUE	EM4512	BLACK
EM4506	GREEN	EM4513	WHITE SOLVENT-BORNE
EM4507	MAHOGANY	EM4514	WHITE WATER-BORNE

Dilution and use

Application	Diluent	Dilution	Vehicle	Quantity	Characteristic of Vehicle
Spray	EM739 Thinner extra-fast	from 1:5 to 1:10	EM10080	Max 20%*	Solvent Vehicle, improves marking pore
	EM716 Thinner medium-slow				
	water				
Rag/paintbrush	EM727 Thinner slow	da 1:5 a 1:10	EM10082	Max 20%*	Solvent Vehicle, improves marking pore
	water		-	-	-
Roller			EM10083	Max 30% *	Adjust the viscosity, possibly diluted with EM727

* The percentage of the vehicle shall be calculated on the amount of dye concentrate

Substrate preparation:	Sanding rough with grain 150
Overcoating:	The dyes of the series --- CSA may undergo color changes tone when overcoated with polyester. therefore recommended the use the insulation before the application of a product polyester.

Storage:

Keep the cans carefully sealed, in a well-ventilated and temperature controlled between 10-30 °C

Deadline:

12 months from date of manufacture when stored according to directions above