



# EM361

## Clear Nitro Sealer

**Main features of the product:**

<ul style="list-style-type: none"> <li>• Applied by spray</li> <li>• Good sandability</li> <li>• General use</li> </ul>	<ul style="list-style-type: none"> <li>• Fast drying</li> <li>• high transparency</li> </ul>
---	--

**Application field** : wooden flat parts, furniture, doors

**Substrate preparation:** sanding wooden items whit grit 180

<b>Application:</b>	Spray gun, airless and airmix		
<b>Mixing preparation:</b>	Product	Code	% weight
	Part "A"	EM361	100
	Thinner	EM713	30÷50

**Chemical-Physical Properties at 20°C**

Solid contents (%)	24±1
Specific gravity (g/cm <sup>3</sup> ) at 20°C	0.97± 0,030
Viscosity DIN 4 (s) at 20°C	110±5

**Application Characteristics**

Quantity recommended per coat	100- 150 g/m <sup>2</sup>
Number of coats recommended	1÷2
Mix. Viscosity ready to use cup DIN 4 at 20°C	17-19 sec

**General indications about the cycle**

	Drying at 20°C(min)	Drying in tunnel at 40°C(min)
Dry dust free	20	15
Imprint free	35÷40	20÷25
Sandable	60÷90	40÷50
Stackable	3÷4 h	2÷3 h

**Storage:**

Keep the cans carefully sealed, in a well-ventilated place and with temperature controlled between 10-30 °C

**Deadline:**

12 months from date of manufacture when stored according to directions above

