



EM362

Clear Nitro Sealer

Main features of the product:

<ul style="list-style-type: none"> • Applied by spray or brush • Good sandability • Fast drying 	<ul style="list-style-type: none"> • High coverage :suitable for both open-pore cycles and closed pore cycles • Good removal resistance • Good transparency
--	--

Field application: wooden flat parts, furniture, doors

Substrate preparation: sanding the wooden items whit grit 180

Application:	Spray gun, airless and airmix		
Mixing preparation:	Product	Code	% weight
	Part "A"	EM362	100
	Thinner	EM713	30÷50

Chemical-Physical Properties at 20°C

Solid contents (%)	29±3
Specific gravity (g/cm ³) at 20°C	0.97± 0,030
Viscosity DIN 4 (s) at 20°C	140±5

Application Characteristics

Quantity recommended per coat	100- 150 g/m ²
Number of hands recommended	Min 1- max 3
Mix. Viscosity ready to use cup DIN 4 at 20°C	17-19 sec

General indications about the cycle

	Drying at 20°C(min)	Drying in tunnel at 40°C(min)
Dry dust free	20	15
Imprint free	35÷40	20÷25
Sanding	60÷90	40÷50
Stackable	3÷4 h	1÷2 h

Storage:

Keep the cans carefully sealed, in a well-ventilated place and with temperature controlled between 10-30 °C

Deadline:

12 months from date of manufacture when stored according to directions above

